

MATERIAL SAFETY DATA SHEET

Page 1

SECTION I - PRODUCT IDENTIFICATION AND PREPARATION INFORMATION

Product Name: CLEAR CRETE
SOLVENT COATING (ACRYLIC)

Chemical Formula: H842-843

Manufacturer: Hawco Products Limited
61 Shaver Street,
Brantford, Ontario. N3T 5V6

Distributor:

Date prepared: September 3, 2014

Emergency Telephone Number: 1-519-759-2443
Canutec 24 Hour Emergency Phone - 613-996-6666, Cellular *666

T.D.G. CLASSIFICATION: FLAMMABLE LIQUIDS N.O.S., UN1993, CLASS 3.3, P.G. II

Hazard Rating

HEALTH:	2	FLAMMABILITY:	3
REACTIVITY:	1	PERSONAL PROTECTION:	F

SECTION II - INGREDIENTS (disclosed as per 29 CFR 1910.1200)

Ingredients	CAS#	Wt%	ACGIH-TLV
XYLENE	1330-20-7	40 - 70	100 ppm
TOLUENE	108-88-3	10 - 30	100 ppm

SECTION III - PHYSICAL DATA

Boiling Point (deg C): 110 INITIAL	Specific gravity: 0.9 - 0.94
Composite Partial Vapour Pressure (mm Hg @ 25C): 5 - 22	Solubility in Water: (20) NIL
pH (as supplied): NAV	Color: CLEAR
Physical State: LIQUID	Odor: AROMATIC ODOR

SECTION IV - FIRE AND EXPLOSION DATA

Flammability: FLAMMABLE
Flash Point (deg C, TCC): 24 (TTC) LEL: 1.0 UEL: 7.0
Hazardous combustion products: CO CO2 Extinguishing Media: CO2, Foam, Water Fog, Dry Chemical
Special Fire Hazards: Shut off fuel supply to fire if possible. Wear self contained breathing apparatus.

SECTION V - REACTIVITY DATA

Conditions for Chemical Instability: STABLE
Hazardous decomposition products: CO, CO2

Incompatible Materials: Strong oxydizers

MATERIAL SAFETY DATA SHEET

Page 2

Chemical Formula: H842-843

SECTION VI - TOXICOLOGICAL PROPERTIES

Route of Entry: Skin Contact, Inhalation Acute, Eye Contact, Ingestion.

EFFECTS OF ACUTE EXPOSURE:

Eye: Severe irritant. May cause corneal burns.

Skin: May cause defatting, drying or cracking.

Inhalation (of mists): May cause irritation to eyes, nose or throat.

Ingestion: May cause irritation and burning to the mouth.

EFFECTS OF CHRONIC EXPOSURE: Eyes, Inhalation and Ingestion are the same as Acute.

Skin: May cause dermatitis.

Carcinogenicity: Not a carcinogen.

SECTION VII- PREVENTATIVE MEASURES

Protective gloves: VITON GLOVES

Eye protection: CHEMICAL GOGGLES

Respiratory protection: NIOSH APPROVED RESPIRATOR

Other protective equipment: EYE WASH STATION

Engineering controls: LOCAL EXHAUST RECOMMENDED. VENTILATION SHOULD BE EXPLOSION PROOF.

Leak and Spill Procedure: ELIMINATE ALL SOURCES OF IGNITION. STOP OR REDUCE DISCHARGE IF SAFE TO DO SO. PREVENT FROM ENTERING WATER COURSES OR SEWERS. VENTILATE ENCLOSED SPACES. SMALL SPILL APPLY ABSORBENT.

Waste disposal: DISPOSE OF ACCORDING TO LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.

Storage Requirements: STORE IN COOL WELL VENTILATED AREA AWAY FROM STRONG OXYDIZERS.

SECTION VIII - FIRST AID

Eye contact: Flush with running water for 15 minutes. Obtain medical attention immediately.

Skin contact: Remove contaminated clothing. Flush skin with running water. Seek medical attention.

Inhalation: Remove to fresh air. Give artificial respiration if needed. Seek medical attention.

Ingestion: Drink 1 or 2 glasses of water or milk. Do not induce vomiting. Seek medical attention.

SECTION IX - PREPARATION DATA OF MATERIAL SAFETY DATA SHEET

Additional information/comments:

Prepared By: HAW

NAP - Not Applicable, NAV - Not Available.

Disclaimer

Information for this material safety data sheet was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this form.