

TECHNICAL DATA SHEET

Product Name: Short Cut
Item Number: H810

Description: As acrylic polymers provide tougher, more durable floor finishes, and the use of special procedures such as spray buffing, burnishing, high-speed buffing, and the mop and shine types of products, there is a need for heavy-duty stripping products to remove stubborn, severe build-ups from resilient floors. Old, oxidized coatings of finish, and repeated layering of waxes and finish tend to hold onto dirt and debris causing dulling and yellowing to floors. To overcome these difficult stripping problems, as well as the problems of incomplete stripping action, the need for multiple stripper applications, and to reduce time consuming and costly labor, this product was formulated to act as an alternative to conventional type ammoniated or solvent based strippers. This product contains heavy-duty emulsifiers, wetting agents for fast penetration, water conditioners to retain its effective-ness in all water conditions, water-miscible solvents, amines, and alkaline cleaning agents. This heavy-duty stripper is for use on stubborn, severe accumulations which are resistant to conventional strippers. The product is pleasantly scented, non-flammable, biodegradable, has rapid re-emulsification activity, and cleans and degreases while it strips. This product provides a clinging action so that it may be used for vertical surface stripping or for use on baseboards. This product may be used to strip waxes and polymer finishes from vinyl, asbestos, linoleum, rubber tile, and on marble and terrazzo.

Directions: Dilution rates vary according to extent of build-up, age of finish, and method of application. See product label for suggested dilution ratios. NOTE: Work floor in sections small enough to prevent stripper from drying out during application. Keep surface wet. Dilute product with water to proper concentration. Apply solution to floor with string mop. Thoroughly wet area and allow product to penetrate and liquefy old finish for 5 to 10 minutes. Agitate surface with floor machine equipped with stripping pad or brush. Pick up liquefied finish with wet/dry vacuum or string mop. Rinse surface thoroughly with clear water and pick up with mop, squeegee, or wet/dry vacuum. Apply new sealer and finish when surface is dry.

DANGER: Contains Butyl Cellosolve and Monoethanolamine. Corrosive. Harmful or fatal if swallowed. Do not take internally. If swallowed, do not induce vomiting. Call physician immediately. Eye and skin irritant. Avoid contact with skin and eyes. If eye contact occurs, flush with water for 15 minutes. If irritation persists, consult a physician. If skin contact occurs, remove contaminated clothing. Wash with soap and warm water. If irritation persists, consult a physician. KEEP OUT OF REACH OF CHILDREN.

Container Disposal: Triple rinse container and discard according to local regulations.

Spill Or Leakage Procedures: Neutralize spilled material with acetic acid & soak up in an inert absorbent. Dispose of in a legal manner.

Product Specifications:

Color: Clear
pH: 11.5 - 12.5
Odor: Butyl
Appearance: Turbid

Hawco Products Ltd
61 Shaver St., Brantford, Ontario
(519) 759-2443 Fax: (519) 758-0371. Toll Free: 1-800-813-9621.
Email: hawco@hawcoproducts.com www.hawcoproducts.com